Surcharge galvanised

Price in €ex VAT

on request

on request





Price List Bunded Fuel Tanks - IBCs, with Vlarem/KIWA/UN/ADR approval





Content IBC	Dimensions	A Standard	B Generator	C Complete	Surcharge
(Liter)	lxwxh (mm)	painted	painted	painted	galvanised
		Price in € ex VAT	Price in € ex VAT	Price in €ex VAT	Price in €ex VAT
200	1140x652x960	on request	on request	on request	on request
400	1060x1192x1090	on request	on request	on request	on request
600	1360x1192x1090	on request	on request	on request	on request
800	1360x1192x1300	on request	on request	on request	on request
995	1560x1192x1300	on request	on request	on request	on request
1150	1740x1192x1260	on request	on request	on request	on request
1600	2275x1192x1260	on request	on request	on request	on request
2000	2190x1192x1500	on request	on request	on request	on request
2400	2486x1192x1500	on request	on request	on request	on request
3000	3090x1192x1500	on request	on request	on request	on request
3000HC	2428x1200x1807	on request	on request	on request	on request

A-version is standard with filling opening 2 ½", level indication tube 1 ½", suction pipe 1", spare socket 2", ventilation with leakage security, probe in 1" socket,

4 lifting eyes, forklift pockets on 2 sides

B-version is A-version, including content meter (starting from 400 Liter) and ½" generator connection (suction + return), both with ball valve

C-version is B-version, stackable (fiiled), from 1150 Liter on with 2 extra ½" generator connections (suction + return), both with ball valve. Forklift pockets on 4 sides.

Tanktrailer for site/agriculture (low speed)



IBC2000 Liter single axle IBC3000 Liter double axle Price in € ex VAT on request on request

Version is B-version. Trailer including fenders, lights and hydraulic breaks.

General technical specifications:

Complies with Vlarem 2 and international traffic norms VLG/ADR. Delivered with Vlarem prototype approval (by AIB-Vinçotte), UN approval and logbook. All IBCs come with overturn safety, with overfill-protection and with pump storage room (30cm). Material thickness 3mm. Removable inner tank.









Pumps for IBCs

Manual pumps

Manual pump K3, 60 Liter/min. Manual pump K5, 90 Liter/min.

Electrical pumps 12 or 24V, 35 Liter/min.

12 or 24V, 85 Liter/min.

Duo 12V-35 I/min. and 24V-65 I/min. 230V 55 Liter/min.

230V 70 Liter/min.

230V 100 Liter/min.

Double pumps

K3 + 12 or 24V, 35 Liter/min.

K3 + Duo 12/24V-35/65 Liter/min.

K3 + 230V, 55 Liter/min.

K5 + 12 or 24V, 85 Liter/min.

K5 + 230V, 72 Liter/min.

K5 + 230V, 100 Liter/min.

A-version is pump without filter B-version is pump with fuel filter

A-version	B-version	C-version				
Price in € ex VAT	Price in € ex VAT	Price in €ex VAT				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
on request	on request	on request				
<u>-</u>						

C-version is pump with fuel filter, K33 (3 digits) counter, incl. grid on floor and nozzle holder.