

OPTIONS FOR WATER-COOLED GENERATING SETS WITH KUBOTA ENGINE			Price in EURO (ex. VAT)
Nr.	Description		
	100	Trailer for New Boy EPS73DE/EP83TDE/EP103DE/EP113TDE/EP230DXE (single axle, unbraked)	on request
	101	Braked trailer for EP183TDE/EP300DXE/EP243TDE/EP400DXE/EP14TDE/EP20TDE/EP20TDE (single axle)	on request
	102a	Braked trailer for EP20TDE/EP34TDE/EP44TDE (twin-axle)	on request
	102b	Braked trailer for EP34TDE/EP44TDE (twin-axle)	on request
	103	4-wheel kit for generating sets New Boy	on request
	104	Forklift kit for generating sets from 7 till 44kVA	on request
	105a	Large tank for New Boy with Z482 (53 liter) / D722 + D902 (58 liter) engine	on request
	105b	Large fuel tank, 150 Liter, bundled, for EP8DE/EP9TDE/EP163DE/EP183TDE/EP300DXE	on request
	105c	Large fuel tank, 400 Liter, bundled, for all "EPS" TYPES till 44kVA	on request
	105d	258 Liter fuel tank (72h at full load) for EP11-3TDE	on request
	105e	368 Liter fuel tank (72h at full load) for EP20TDE	on request
NEW	105f	732 Liter fuel tank (72h at full load) for EP34TDE / EP44TDE / EPUS20TDE	on request
	106a	Three-way cocks for connection to external fuel tank, quick couplings included	on request
	106b	Stronger fuel pump (12V DC) for option 106a	on request
	107a	Minimum fuel level switch with control lamp	on request
	107b	Liquid level switch (alarm) in chassis (bund) for EP11-3TDE, EP20TDE/EP34TDE/EP44TDE	on request
	108a	Leroy Somer LSA40 and LSA42.3 alternator protection "system 4" for severe industrial environment, marine environment and coastal area without projections, relative humidity > 95% (for EP(S)(R)20/34/44TDE)	on request
	108b	Leroy Somer LSA40 and LSA42.3 alternator protection "system 6" for corrosive industrial environment, marine environment and coastal area with projections, relative humidity > 95% (for EP(S)(R)20/34/44TDE)	on request
	108c	Glass fiber winding (25% derate) for LSA40 and LSA42.3	on request
	109	Battery charger DSE9150 12V 3A (including 230V male socket in control panel) for EP11-3TDE, EP20TDE/EP34TDE/EP44TDE	on request
	110	Battery on/off switch	on request
	111a	Insulation protection "IB-Protector"	on request
	111b	Insulation protection Bender IR423-D43-2	on request
NEW	111c	Insulation protection Bender ISORW425-D4W-4 (for sensitive equipment with frequency-controlled drives)	on request
NEW	111d	Sensitive residual current monitor (up to 24kVA): earth leakage protection, type B, 40A, 30mA, 4P (183004440)	on request
NEW	111e	Sensitive residual current monitor (up to 40kVA): earth leakage protection, type B, 63A, 30mA, 4P (183004463)	on request
	112	Ammeter	on request
	113	Frequency meter	on request
	114	Voltmeter switch	on request
	115	Remote control 5m (all types till 24kVA)	on request
	116	Remote control for EP30DE/EP34TDE/EP44TDE/EP11-3TDE/EP20TDE/EP34TDE/EP44TDE, cable not included	on request
	117a	Remote control, wireless, till 50m (all types till 24kVA)	on request
	117b	Remote control, wireless, till 50m (for EP30DE/EP34TDE/EP44TDE/EP11-3TDE/EP20TDE/EP34TDE/EP44TDE)	on request
	118	Star-delta switch 32A 230/400V (up to 14kVA), CEE-socket 32A 5p 230V included	on request
	119	Star-delta switch 63A 230/400V (up to 24kVA), CEE-socket 63A 5p 230V included	on request
	120	ECO-throttle (Automatic Idle System) - different types on request	on request
	121a	Manual switch mains/0/generator 32A 4-poles, in plastic box, not assembled	on request
	121b	Manual switch mains/0/generator 63A 4-poles, in plastic box, not assembled	on request
NEW	121c	Manual switch mains/0/generator 100A 4-poles, in plastic box, not assembled	on request
	123	Automatic Start/Stop System in case of mains failure (up to 9kVA 230V or 17kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 130, without standard control panel on generator! See also p.18	on request
	124	Automatic Start/Stop System in case of mains failure (up to 16kVA 230V or 31kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 130, without standard control panel on generator! See also p.18	on request
	125	Automatic Start/Stop System in case of mains failure (up to 22kVA 230V or 42kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 130, without standard control panel on generator! See also p.18	on request
	126	Automatic Start/Stop System in case of mains failure (up to 46kVA 230V or 87kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 130, without standard control panel on generator! See also p.18	on request
	127	Remote monitoring (web-based control) by DSE890 for laptop / PC / smart phone / tablet (for EP30DE/EP34TDE/EP44TDE/EP11-3TDE/EP20TDE/EP34TDE/EP44TDE)	on request
	128	GSM 3G antenna for option 127	on request
	129	GPS antenna for option 127	on request
	130	Module "three-phase mains control" for option 123, 124, 125 and 126	on request
	131a	Automatic Start/Stop System with PDM1 or DSE3110 via external contact. See also p.18	on request
	131b	Automatic Start/Stop System with DSE4520 via external contact.	on request
	132	Battery controller unit 12V (only to be combined with option 131)	on request
	133	Automatic Start/Stop System on demand	on request
	134	Oil pan heater 230V	on request
	135	Coolant heater for generating sets with Z482/D722/D902/D1105/V1505/D1703/V2203/V3300/V3800DIT engine	on request
	136a	Minimum water level switch for coolant expansion tank	on request
	136b	Minimum level switch for radiator coolant	on request
	136c	Automatic engine oil level maintainer (Murphy LM500-TF), oil tank included (for EP20TDE/ EP34TDE/EP44TDE)	on request
	137	Spark arrestors (ATEX approved or Non-ATEX approved)	on request
	138	Chalwyn valve (air intake shut down valve)	on request
	139	Welding cables 35mm ² (2 x 5m) for welder EP230DXE	on request
	140	Welding cables 50mm ² (2 x 10m) for welder EP230DXE, EP300DXE and EP400DXE	on request
	141a	Special RAL color for EPS / EPRS versions (silenced)	on request
	141b	Extra epoxy primer coating before polyester final coating, for EPS / EPRS / EPUS versions (silenced)	on request

Other options on request