

OPTIONS FOR AIR-COOLED GENERATING SETS 3000rpm			Price in EURO (ex. VAT)
Nr.	Description		
	1a	4-wheel kit (2 to 16kVA/up to max. 154kg)	on request
	1b	2-wheel kit (2 to 16kVA/up to max. 154kg)	on request
	1c	Surcharge for pneumatics per axle for option 1a and 1b	on request
	2a	2-wheel kit with pneumatic wheels 300mm for EP16000E/EP20000TE	on request
	2b	2-wheel kit with pneumatic wheels 250mm for EPG10000/EPG12000TE/EPG12000E/EPG15000TE	on request
	3	4-wheel kit with 4 swivel castors of which 2 with locking device (only for EPS models)	on request
	4a	2 lifting bars (till max. 100kg)	on request
	4b	2 lifting eyes (only for EPS models)	on request
	5a	AVR control (automatic voltage regulator) from 3 up to 8kVA	on request
	5b	AVR control (automatic voltage regulator) from 10 up to 16kVA	on request
	6	Thermal magnetic protection 1 x 230V	on request
	7	Thermal magnetic protection 3 x 400V	on request
	8	Earth leakage protection, type A, 1 x 230V (30mA) (except for EP3300-11)	on request
	9	Earth leakage protection, type A, 3 x 400V (30mA)	on request
	10	Earth pin with 4 meter earth-cable 16mm ²	on request
NEW	11a	Insulation protection "IB-Protector" 230V with thermal magnetic protection	on request
	11b	Insulation protection Bender IR423-D43-2, 230V, with thermal magnetic protection	on request
	12a	Insulation protection "IB-Protector" 400V with thermal magnetic protection	on request
NEW	12b	Insulation protection Bender IR423-D43-2, 400V, with thermal magnetic protection	on request
	13a	Star-delta switch 20A 230/400V, CEE-socket 5P 16A 230V included (up to 8,5kVA standard types, other types on request)	on request
	13b	Star-delta switch 32A 230/400V, CEE-socket 5P 32A 230V included (up to 16kVA standard types, other types on request)	on request
	14	Hour counter	on request
	15	Voltmeter	on request
	16	Volt- and ammeter 1 x 230V	on request
	17	Voltmeter, ammeter and frequency meter 1 x 230V	on request
	18	Voltmeter with voltmeter switch and 3 ammeters 3 x 400V	on request
	19	Voltmeter with voltmeter switch, 3 ammeters and frequency meter 3 x 400V	on request
	20	12 Volt DC (10A) battery charger for generators up to 7kVA / 230V with thermal magnetic protection	on request
	21	Remote control 5m (Honda petrol engines/electric start) incl. option 25	on request
	22	Remote control 5m (diesel engines/electric start) incl. option 26	on request
	23	Remote control, wireless, up to 50m (petrol + diesel engines/electric start) excl. options 25/26	on request
	24	ECO-throttle (Automatic Idle System) - different types on request	on request
	25	Electric choke (for gasoline generators with Honda + B&S Vanguard engine/electric start)	on request
	26a	Stop solenoid Hatz 1B types diesel/electric start	on request
	26b	Stop solenoid Yanmar L48/70/100 diesel/electric start	on request
	27	Manual switch mains/0/generator 20A 4-poles, in plastic box, not assembled (10kVA 230V / 15kVA 400V)	on request
	28	Automatic Start/Stop System in case of mains failure (up to 9kVA 230V or 17kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 25/26 and 30, without standard control panel on generator! See also p.18	on request
	29	Automatic Start/Stop System in case of mains failure (up to 16kVA 230V or 31kVA 400V), with single phase mains control, supplied in TN-S earthing system, including earth leakage protection and thermal magnetic protection, with 3 meter cable, excl. option 25/26 and 30, without standard control panel on generator! See also p.18	on request
	30	Module "three-phase mains control" for option 28 and 29	on request
	31	Automatic Start/Stop System via external contact (excl. option 25/26). See also p.18	on request
	32	Battery controller unit 12V (only to be combined with option 31)	on request
	33	Automatic Start/Stop System on demand (excl. option 25/26)	on request
	34	Oil pan heater 230V	on request
	35	Kit jerrycan 20 liter with carrier frame and membrane pump (GX270/390)	on request
	36	Large tank (stainless steel) 11 liter (GX160/200) - 20 liter (GX270/390) in frame	on request
	37	Flexible exhaust tube 2m (adapter for muffler included)	on request
	38	LPG / propane version for Honda GX160/200/270/390 recoil start (regulator included)	on request
	39a	LPG / propane version for Honda GX160/270/390 electric start (regulator included)	on request
	39b	LPG / propane version for Honda GX690H-VXC4 electric start (regulator included) - EP9000GE + EP11000GTE	on request
	40	Welding cables 25mm ² (2 x 5m) for AC welding generators	on request
	41	Welding cables 35mm ² (2 x 5m) for DC welding generators up to 250A	on request
	42	Welding cables 50mm ² (2 x 10m) for DC welding generators up to 300A	on request
	43	Protection cover (red / up to 16kVA, standard types, open frame)	on request
	44	Oil drain pump (only for EPS models)	on request
	45	Europower sirometer (mechanical revolution counter / frequency meter) for after sales service	on request
	46	T-shirt Europower	on request

Other options on request